

MAIN FEATURES


Encoder series designed for use in harsh environments with high mechanical resistance requirements. The model 90A can be mounted synchronous flange and fixing clamps while the model 115A has a tachometer generator REO-444 type compatible flange.

- 3 channel encoder (A / B / Z) up to 10000 ppr
- Power supply up to +30 V DC with various electrical interfaces available
- Output frequency up to 800 kHz
- Cable or connector output
- Metal cover for heavy duty applications
- Solid shaft diameter up to 11 mm
- Mounting by synchronous or REO-444 flange




ORDERING CODE	EMI	90A	500	S	5/30	P	8	X	X	M	R	.162	+XXX
SERIES magnetic incremental encoder series EMI													
MODEL synchronous flange ø 40 mm 90A flange REO-444 115A													
RESOLUTION ppr from 1 to 10000 refer to the available pulses list													
ZERO PULSE without zero pulse S with zero pulse Z													
POWER SUPPLY (with L electrical interface) 5 V DC 5 5 ... 30 V DC 5/30													
ELECTRICAL INTERFACE NPN open collector C push-pull P line driver L power supply 5/30 V DC - output RS-422 RS													
SHAFT DIAMETER (mod. 90A) mm 8 (mod. 90A) (3/8") mm 9,52 mm 10 (mod. 115A) mm 11													
ENCLOSURE RATING IP 54 shaft side / IP 67 cover side X IP 66 shaft side (mod. 90A) - IP 65 shaft side (mod. 115A) / IP 67 cover side S													
OPTION to be reported X													
OUTPUT TYPE cable (standard length 1.5 m) P preferred cable lengths 2 / 3 / 5 / 10 m, to be added after DIRECTION TYPE (eg. PR5) MIL plug connector M JIS-C-5432 IP40 plug connector J													
DIRECTION TYPE axial A radial R													
SOCKET socket not included .162 to be reported only with connector output (eg. MR.162), for socket see Accessories													
VARIANT custom version XXX													

90A




115A




fixing clamps not included, please refer to Accessories

90A WITH AXIAL OUTPUT



115A WITH AXIAL OUTPUT



recommended mating shaft tolerance H7
dimensions in mm

ELECTRICAL SPECIFICATIONS

Resolution	from 1 to 10000 ppr
Power supply¹	5 = 4,5 ... 5,5 V DC 5/30 = 4,5 ... 30 V DC (reverse polarity protection)
Power draw without load	0,8 W max
Max load current	C / P = 50 mA / channel L / RS = 20 mA / channel
Electrical interface²	NPN open collector (AEIC-7273, pull-up max +30 V DC) push-pull / line driver HTL (AEIC-7272 or similar) line driver RS-422 (AELT-5000 or similar)
Max output frequency	800 kHz
Counting direction	A leads B clockwise (shaft view)
Index signal	180°e (gated A)
Startup time typical	10 ms
Accuracy	< 0,3° at +20°C (+68°F) ± 0,5° in the operating temperature range
Hysteresis	0,70° up to 256 ppr 0,35° from 257 ppr to 10000 ppr
Mean time to dangerous failure (MTTF_d)³ according to EN ISO 13849-1	275 years
Mission time (T_m)³	20 years
Diagnostic coverage (DC)³	0%
Cable type	shielded - fixed installation conductors section 0,22 mm ² / AWG 24 bending radius min 60 mm
Electromagnetic compatibility	according to 2014/30/EU directive
RoHs	according to 2011/65/EU directive
UL / CSA	file n. E212495

MECHANICAL SPECIFICATIONS

Shaft diameter	∅ 8 / 9,52 (3/8") / 10 / 11 mm
Enclosure rating IEC 60529	X = IP 54 shaft side / IP 67 cover side S = IP 66 shaft side / IP 67 cover side (mod. 90A) S = IP 65 shaft side / IP 67 cover side (mod. 115A)
Max rotation speed	6000 rpm
Max shaft load⁴	200 N (45 lbs) axial / radial
Shock	50 G, 11 ms (IEC 60068-2-27)
Vibration	10 G, 10 ... 2000 Hz (IEC 60068-2-6)
Moment of inertia	3,5 x 10 ⁻⁶ kgm ² (83 x 10 ⁻⁶ lbf ²)
Starting torque (at +20°C / +68°F)	< 0,02 Nm (2,83 Ozin) with X enclosure rating < 0,06 Nm (8,50 Ozin) with S enclosure rating
Bearing stage material	aluminum
Shaft material	stainless steel
Housing material	painted aluminum
Bearings	n.2 ball bearings
Bearings life	10 ⁹ revolutions
Operating temperature^{5,6}	-25° ... +85°C (-13° ... +185°F)
Storage temperature⁶	-25° ... +70°C (-13° ... +158°F)
Weight	350 g (12,35 oz) 450 g (15,87 oz) with metal cover

¹ as measured at the transducer without cable influences

² for further details refer to OUTPUT LEVELS on TECHNICAL BASICS section

³ this product is not a safety component, for further details refer to TECHNICAL BASICS section

⁴ maximum load for static usage

⁵ measured on the transducer flange

⁶ condensation not allowed

PREFERRED RESOLUTIONS


2 - 4 - 5 - 6 - 8 - 10 - 12 - 16 - 20 - 30 - 40 - 50 - 60 - 80 - 90 - 100 - 125 - 128 - 200 - 250 - 256 - 360 - 400 - 500 - 512 - 720 - 1000 - 1024 - 1440 - 2000 - 2048 - 3600 - 4096 - 5000 - 7200 - 10000

please directly contact our offices for other pulses


CONNECTIONS

Function	Cable C / P	Cable L / RS	7 pin J C / P	7 pin J L / RS no Zero	7 pin M C / P	7 pin M L / RS no Zero	10 pin J L / RS with Zero	10 pin M L / RS with Zero
+V DC	red	red	6	4	F	D	4 - 5	D - E
0 V	black	black	1	6	A	F	6	F
A+	green	green	3	1	C	A	1	A
A-	/	brown or grey	/	3	/	C	7	G
B+	yellow	yellow	5	2	E	B	2	B
B-	/	orange	/	5	/	E	8	H
Z+	blue	blue	4	/	D	/	3	C
Z-	/	white	/	/	/	/	9	I
⏏	shield	shield	7	7	G	G	10	J

J connector (7 pin)
JIS-C-5432 IP40 Size 16
front view



M connector (7 pin)
Amphenol MS3102-E-16-S
front view



J connector (10 pin)
JIS-C-5432 IP40 Size 16
front view



M connector (10 pin)
Amphenol MS3102-E-18-1
front view

